

FORM PTO-1390 (REV 10-96)		U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE		ATTORNEY'S DOCKET NUMBER 31767	
TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371				U.S. APPLICATION NO. (If known, see 37 CFR 1.5) 09/319626	
INTERNATIONAL APPLICATION NO. PCT/FR97/02299		INTERNATIONAL FILING DATE 15 December 1997 (15.12.97)		PRIORITY DATE CLAIMED 16 December 1996 (16/12/96)	
TITLE OF INVENTION METHOD AND DEVICE FOR REMOTE IDENTIFICATION					
APPLICANT(S) FOR DO/EO/US CROCHON, Elisabeth; VACHERAND, Francois					
Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:					
1. <input checked="" type="checkbox"/> This is a FIRST submission of items concerning a filing under 35 U.S.C. 371. 2. <input type="checkbox"/> This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. 371. 3. <input type="checkbox"/> This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1). 4. <input checked="" type="checkbox"/> A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date. 5. <input checked="" type="checkbox"/> A copy of the International Application as filed (35 U.S.C. 371(c)(2)) a. <input type="checkbox"/> is transmitted herewith (required only if not transmitted by the International Bureau). b. <input checked="" type="checkbox"/> has been transmitted by the International Bureau. c. <input type="checkbox"/> is not required, as the application was filed in the United States Receiving Office (RO/US). 6. <input checked="" type="checkbox"/> A translation of the International Application into English (35 U.S.C. 371(c)(2)). 7. <input checked="" type="checkbox"/> Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3)) a. <input type="checkbox"/> are transmitted herewith (required only if not transmitted by the International Bureau). b. <input type="checkbox"/> have been transmitted by the International Bureau. c. <input type="checkbox"/> have not been made; however, the time limit for making such amendments has NOT expired. d. <input checked="" type="checkbox"/> have not been made and will not be made. 8. <input type="checkbox"/> A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)). 9. <input checked="" type="checkbox"/> An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)). 10. <input checked="" type="checkbox"/> A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).					
Items 11. to 16. below concern document(s) or information included:					
11. <input checked="" type="checkbox"/> An Information Disclosure Statement under 37 CFR 1.97 and 1.98. 12. <input checked="" type="checkbox"/> An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included. 13. <input type="checkbox"/> A FIRST preliminary amendment. <input type="checkbox"/> A SECOND or SUBSEQUENT preliminary amendment. 14. <input type="checkbox"/> A substitute specification. 15. <input type="checkbox"/> A change of power of attorney and/or address letter. 16. <input checked="" type="checkbox"/> Other items or information: Copy of International Preliminary Examination Report.					
				"Express Mail" mailing label number <u>EL106191266US</u>	
				Date of Deposit <u>6/9/99</u>	
I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. § 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.					
<u>Paula Almasy</u> Printed Name of Person Mailing Paper or Fee					
<u>Paula Almasy</u> Signature of Person Mailing Paper or Fee					

PCT Applicant's Guide – Volume II – National Chapter – US

Form PTO-1390 (REV 10-96) page 2 of 2

METHOD AND DEVICE FOR REMOTE IDENTIFICATION

DESCRIPTION

5 The invention relates to a method for the remote identification of objects referred to as labels, normally movable, by an interrogation apparatus whose interrogation field they can enter before leaving in a random fashion. It also relates to a corresponding installation.

10 Such methods can be applied for example to the checking of personnel access, or the identification of luggage or objects on a conveyor belt or products or tools on a production line; other usual applications relate to payment for goods at a supermarket checkout
15 or motorway tolls, by automatically debiting an account. A prior example is described in the patent WO-A-92-22040 of the same applicant and shows how labels present in the interrogation field were caused by the interrogator to successively supply their codes,
20 which made it possible to identify them. The labels thus responded to a control signal of the interrogator and, when a label detected that the code currently being identified was different from its own, it inhibited itself momentarily, and the identification
25 cycle continued with the other labels until there remained only one uninhibited label corresponding to the identified label. Inhibition of the labels means in fact that they no longer emit a signal and therefore become mute. At the end of an identification cycle, at
30 a single command from the interrogator, the identified label was inhibited definitively and the other labels lifted their momentary inhibition. The identification procedure was reinitialised in order thus to identify another label. These operations were repeated as many

times as necessary for identifying all the labels separately.

5 This method was subject to certain failings, the most important of which is perhaps that it was purely passive, that is to say it merely noted the presence of labels in the interrogation field, making it possible only to record this presence or to indicate it to another system or an operator. It was also fairly slow: in particular, an off-load interrogation cycle 10 was always implemented after all the labels had been identified in order to ensure that there were no more of them. Because of this slowness, the use of this method in a dynamic environment carries the risk of not identifying any labels passing through the 15 interrogation field too quickly.

Taking these circumstances into consideration, an essential object of the invention is therefore to allow the application of an identification method of the type of the prior patent to more numerous situations, in 20 which the labels can be movable, and where the interrogator carries out specific processings on the label: a reading of the content of the label distinct from the code and/or the writing of information. It will thus be possible to update the conditions for access to the label carriers, to check the correct 25 routing of luggage or to enter a passage time on a label comprising a historical file. Another object of the invention is to accelerate the identification process in order to make it more effective and to reduce the risk of a lack of check on a label passing 30 too quickly.

In its most general form, the method for the remote identification of labels provided with a distinctive code according to the invention - the 35 labels being situated in a field of an interrogation

apparatus and the interrogation consisting of sendings and receivings of signals between the interrogator and labels, the labels being able to be inhibited - comprises steps of identification of the labels by successively reading their codes and then final inhibition of the identified labels as long as they remain in the field; it is characterised in that it comprises, between the identification and final inhibition of a label, a passage of information between the interrogator and this label, the other labels being temporarily inhibited. The passage of information is advantageously controlled by the sending of an identification stoppage signal by the interrogator, the identification stoppage signal containing all or part of the code of the said label.

Before the label identification steps, which consist of successively reading their codes in fragments, preferably bit by bit, an improvement to the invention can consist of a prior identification step in which the labels which are not definitively inhibited send together all their code in response to a signal of the interrogator. This prior identification step is particularly adapted to a single-label context, a context which is frequent in the type of application envisaged. This improvement then avoids interrogation fragment by fragment. Another improvement consists of optimising the procedure of the prior patent of identification fragment by fragment. At each identification step, the sending of the sequence of fragments will take place either from the least significant fragment to the most significant fragment, or vice versa.

The identification device therefore comprises an interrogation apparatus and labels, which each comprise signal transceivers, converters converting signals into

logic information and vice versa and logic processing means for the information; the labels also each comprise a distinctive code, and the interrogation apparatus a catalogue of signals. The means by which the invention is implemented can comprise signals added to the catalogue, such as a signal initiating a passage of information between the interrogator and the identified label; a signal causing at least some of the labels to send their entire code simultaneously; or two signals controlling the sending of codes by successive fragments by the labels, the fragments following each other in one order or the reverse order according to the command chosen.

Advantageously, the fragment corresponds to a binary element or bit.

The invention will now be described in more detail with the help of the following figures:

- Figure 1 depicts a diagram of the invention depicting a practical situation;
- Figure 2 depicts side by side the main elements of the interrogation apparatus and of a label; and
- Figures 3 and 4 depict the operating diagrams of the interrogation apparatus and labels.

Figure 1 therefore depicts an interrogator 1 able to communicate with labels in the range of an identification field 2 whose limits are defined amongst other things by the power of the sending elements and the sensitivity of the receivers of the interrogator 1. Labels E pass in a random flow, continuous or otherwise, in front of the interrogator 1 and pass through the identification field 2; here five of them have been shown, referenced from E0 to E4, where the first E0 has already left the identification field 2, the following three E1 to E3 are situated therein and the last one E4 is to enter it. The labels E are fixed

to objects or persons, not depicted, according to the application chosen, and the interrogator 1, symbolised here by a plate, can take a different form; it can be a case of an arch delimiting an opening under which the carriers of labels E are obliged to pass.

Figure 2 will now be commented on. The interrogator comprises: a transceiving resonant circuit 5, comprising in particular an antenna and constituting the primary circuit of an inductive coupling between the interrogator 1 and the labels E; a modulator 6 and a demodulator 7 for converting a signal pattern into a modulated signal transmitted by the resonant circuit 5, and vice versa; logic means 8 for controlling the steps of the identification transaction between the interrogator 1 and the labels E, producing binary signals which they next convert into single patterns supplied to the modulator 6, and finally collecting the signals which they receive from the demodulator 7 and which come from the label E in order to convert them into binary information; finally, there is a radiofrequency signal generating module 9, connected to the modulator 6, which controls the functioning of the labels E.

The latter also comprise a resonant circuit 10, having an antenna forming the secondary circuit of the inductive coupling between the interrogator and the label and which is coupled to a power supply recovery module 11 responsible for rectifying a carrier transmitted continuously by the interrogator 1, and for filtering and stabilising it at the nominal operating voltage of the electronics of the label E in order to recover the energy necessary for the functioning of the label; a zeroing module 12, verifying that a sufficient supply voltage is applied to the label E for a sufficiently long time, which indicates that the label

E has entered the interrogation field 2 and then enables the zeroing module 12 to initialise the logic means of the label E in order to put them in a state to fulfil their role on the information exchange transaction with the interrogator 1; a clock recovery module 13 for timing the transaction, and which arrives at this result by dividing the frequency of the carrier; a demodulator 14 extracting, from the signal received by the resonant circuit 10, a signal which can be used by the logic means of the label; and a modulator 15 for transmitting information from the label E to the interrogator 1.

These modules 11 to 15 are also connected to logic means 16 responsible for the transaction, the interpretation of the signals received from the interrogator 1, the sending of the requested signals and the sequencing of the transaction. The logic means 16 can control a temporary inhibition flip-flop 17 (also referred to as momentary inhibition) and a definitive inhibition flip-flop 18, and they finally communicate with a memory 19, which can be an EEPROM memory (a read only memory which is electrically programmable and erasable in read mode and possibly in write mode).

These logic means 16 and the logics 8 also afford the management of the timing necessary to the exchanges between the interrogator and the labels. This timing is effected by means, for example, of counters associated with clocks.

The information exchanged corresponds to binary signals. In all cases, the labels E are caused to give their codes, and, depending on what is requested of them, all at one go or bit by bit. According to a first example embodiment using a Huffman-type coding, the interrogator 1 sends six signals, four of which

have three data bits and two of which have two data bits, which are indicated in Table I.

TABLE I

Signals	Meaning
111	Start of interrogation
110	Start of identification sequence commencing with the most significant bit
100	Start of identification sequence starting with the least significant bit
101	Confirmation of identified label code
00	Reading of following bit, no label having its previous bit at 1
01	Reading of following bit, at least one label having its previous bit at 1

5 The start of interrogation signal causes all the labels E which have not been definitively inhibited to send their codes simultaneously.

10 The two start of sequence signals cause the labels E which have not been definitively inhibited to give their code bit by bit, either commencing with the most significant bit (reading the code in the natural direction) or commencing with the least significant bit (reading the code from right to left). The code confirmation signal, which is followed by the code of the identified label, announces that a particular transaction will take place with this label; this

15 confirmation signal corresponds to the transaction initialisation signal. Finally, the information of type 0 and 1 indicates that the bits equal to 1 have not been found, or on the contrary that they have been

20 found, in the codes of the labels currently being read. On reception of this information, the labels whose previously read bit does not correspond to this said information sent by the interrogator are temporarily inhibited.

The identification method will now be given in Table II with the example of Figure 1, which will make it possible to explain it clearly; the labels E1 to E4 have 00011, 01100, 01010 and 00111 as their code respectively; it is unnecessary to give the code of the label E0, which has left the interrogation field 2 and will no longer re-enter it. E4 will enter the field of the interrogator during the interrogation sequence

TABLE II

Action of interrogator 1	State of all the labels E	Action of the labels E
Start of interrogation (signal 111)	E1, E2, E3 in interrogation field 2	E1, E2 and E3 return their code
Start of identification sequence at most significant bit (signal 110)		No response: E1, E2 and E3 have their first bit at 0
Information of type 0 (signal 00)		E2 and E3 send, their second bit being at 1
Information of type 1		E1 is temporarily inhibited; E2 sends, its third bit being at 1
Information of type 1		E3 is temporarily inhibited; no sending, the labels still active (E2) having their fourth bit at 0
Information of type 0		No sending, the labels still active (E2) having their

		fifth bit at zero
Confirmation of code 01100 (signal 10101100)		The label E2 recognises its code
Exchange of information with label E2		
Start of interrogation	E2 becomes inactive and E1 and E3 become active again	E2 is definitively inhibited, E1 and E3 send their code
Start of identification sequence at least significant bit (signal 100)		E1 sends, its fifth bit being equal to 1
Information of type 1		E3 is temporarily inhibited, E1 sends
Information of type 1		No sending
Information of type 0		No sending
Information of type 0	E4 enters the interrogation field	No sending
Confirmation of code 00011		The label E1 identifies its code
Exchange of information with label E1		
Start of interrogation	E1 becomes inactive, E3 becomes active again, E4 becomes active	E1 is definitively inhibited; E3 and E4 send their code
Start of identification sequence at most significant bit		No response
Information of type 0		E3 sends
Information of type 1	E1 leaves interrogation field 2	E4 is temporarily inhibited; no sending
Information of type 0		E3 sends
Information of type 1		No sending
Confirmation of code 01010		E3 identifies its code

Exchange of information with label E3		
Start of interrogation	E3 becomes inactive, E4 becomes active again	E3 is definitively inhibited; E4 sends its code
Confirmation of code 00111		E4 identifies its code
Exchange of information with label E4		
Start of interrogation	E4 becomes inactive	E4 is definitively inhibited

A clearer and more general presentation of the method is given by the flow diagrams in Figures 3 and 4 respectively with regard to the interrogator and the label.

Each identification cycle commences with a start of interrogation signal, in which the non-inhibited labels send all their identification code all at one go. This step makes it possible to recognise whether a single signal is sent, or whether on the other hand there is a superimposition of signals. In the first case, which corresponds to that of a single label E still to be identified in the interrogation field 2, the identification is immediate and it is possible to commence the passage of information between this label and the interrogator 1 without any other formality; in the contrary case, a successive identification of the labels E is carried out according to a method which resembles that of the prior patent of the applicant. This method entails a bit by bit reading of the codes and comprises sending of signals of type 0 or 1 according to whether the previously read bits of the labels currently being identified were all equal to 0 or not. When a signal of type 1 is sent, the labels

whose previously read bit was equal to 0 are temporarily inhibited, and the interrogation continues only on the others. An important advantage of the invention is that the start of interrogation signal avoids having recourse to the identification sequence when there is only one label, and even better when there are no longer any at all, which was essential in the prior method to ensure that all the labels have indeed been read.

10 The alternation of the start of sequence signals for controlling code readings in both directions has the effect of not favouring the systematic identification of the labels E whose code is high, which can allow the others time to leave the
15 interrogation field 2 without having been identified. The label E whose code commences with three zeros would thus take a long time to be identified if the reading of the most significant bits was always commenced with, since it would be read after the labels E2, E3 and even
20 E4, and could therefore leave the interrogation field unperceived. When all the labels E have been identified and inhibited definitively, the start of interrogation signal does not give rise to any response and the interrogator 1 pauses before sending it once
25 again whilst awaiting a new label E entering the interrogation field 2.

CLAIMS

1. A method for the remote identification of labels (E) provided with a distinctive code and situated in a field (2) of an interrogation apparatus (1), by sending and receiving signals between the interrogator and the labels, the labels being able to be inhibited, comprising steps of identification of the labels by successively reading their code and then of final inhibition of the identified labels as long as they remain in the field (2), characterised in that it comprises, between the identification and final inhibition of a label, a passage of information between the interrogator and the said label, the other labels being temporarily inhibited.

2. A remote identification method according to Claim 1, characterised in that the passage of information is controlled by the sending of an identification stoppage signal by the interrogator, the identification stoppage signal containing at least all or part of the code of the said label.

3. A remote identification method according to Claim 1, characterised in that it includes, before a step of identification of the labels fragment by fragment, a step of prior identification adapted to a single-label context affording rapid identification of a single label on a single signal of the interrogator.

4. An identification method according to Claim 1, characterised in that the codes are read either in one direction or the other each time the identification steps are resumed.

5. A device for the remote identification of labels by an interrogation apparatus, the interrogation apparatus (1) and the labels (E) comprising signal transceivers (5, 10), converters (6, 7, 14, 15)

converting the signals into logic information and vice versa, and logic means (8, 16) for processing the information, the labels each comprising a distinctive code and a memory, and the interrogation apparatus comprising a signal catalogue, characterised in that the signal catalogue comprises a signal initiating a passage of information between the interrogator and the identified label.

6. A remote identification device according to Claim 5, characterised in that the signal catalogue comprises a prior identification signal causing at least some of the labels to send all their codes simultaneously.

7. A remote identification device according to Claim 5, characterised in that the signal catalogue comprises two signals demanding reading of the code in fragments, one of the signals demanding reading in one direction and the other signal demanding reading in an opposite direction.

ABSTRACT

This method of identification between an interrogation system (1) such as an arch and labels (E) placed on objects to be identified and called upon to pass through the interrogation field (2) functions by the sending of control signals from the interrogator (1) to the labels (E) so that the latter transmit their codes. The known interrogation mode in which the codes are supplied bit by bit and the labels responding simultaneously are inhibited in turn so that only one is active and identified at any one time, is preceded by an identification test during which all the labels send their code at one go all at the same time, which allows immediate identification if only one label is present. When a label has been identified, the interrogator (1) isolates it in order to exchange particular information with it.

Figure 1




FIG.1





FIG. 2

3 / 4

FIG. 3






FIG. 4

B 12616.3 JCI

Declaration, Power Of Attorney and Petition

Page 1 of 3

WE (I) the undersigned inventor(s), hereby declare(s) that :

My residence, post office address and citizenship are as stated below next to my name,

We (I) believe that we are (I am) the original, first, and joint (sole) inventor(s) of the subject matter which is claimed and for which a patent is sought on the invention entitled

"METHOD AND DEVICE FOR REMOTE IDENTIFICATION"

the specification of which

- ☐ is attached hereto.
- ☐ was filed on _____
as Application Serial No. _____
and amended on _____
- ☒ was filed as PCT international application
Number PCT/FR97/02299
on December 15, 1997
and was amended under PCT Article 19
on November 13, 1998

We (I) hereby state that we (I) have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

We (I) acknowledge the duty to disclose information known to be material to the patentability of this application as defined in Section 1.56 of Title 37 Code of Federal Regulations.

We (I) hereby claim foreign priority benefits under 35 U.S.C. § 119 (a)-(d) or § 365 (b) of any foreign application(s) for patent or inventor's certificate, or § 365 (a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed. Prior Foreign Application (s)

Application No.	Country	Day/month/Year	Priority Claimed
96/15434	FRANCE	16 DECEMBER 1996	<input checked="" type="checkbox"/> YES <input type="checkbox"/> NO
_____	_____	_____	<input type="checkbox"/> YES <input type="checkbox"/> NO
_____	_____	_____	<input type="checkbox"/> YES <input type="checkbox"/> NO
_____	_____	_____	<input type="checkbox"/> YES <input type="checkbox"/> NO

We (I) hereby claim the benefit under Title 35, United States Code, § 119 (e) of any United States provisional application(s) listed below.

(Application Number)

(Filing Date)

(Application Number)

(Filing Date)

We (I) hereby claim the benefit under 35 U.S.C. §120 of any United States application(s), or § 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR § 1.56 which became available between the filing date of prior application and the national or PCT International filing date of this application.

Application Serial No.

Filing Date


Status (pending, patented,
abandoned)

17 And we (I) hereby appoint : Charles B. Gordon, Registration Number 16,923; William C. McCoy, Registration Number 16,885; Louis V. Granger, Registration Number 15,999; William A. Gail, Registration Number 17,409; Richard H. Dickinson Jr, Registration Number 18,622; Thomas P. Schiller, Registration Number 20,677; David B. Deiona, Registration Number 22,841; Joseph J. Corso, Registration Number 25,845; Howard G. Shimola, Registration Number 26,232; Jeffrey J. Sopko, Registration Number 27,676; John P. Murtaugh, Registration Number 34,226; James M. Moore, Registration Number 32,923; David E. Spaw, Registration Number 34,732; Michael W. Garvey, Registration Number 35,878; Paul R. Katterle, Registration Number 36,563; Richard M. Mescher, Registration Number 38,242 and Mark E. Bandy, Registration Number 35,788; our (my) attorneys, with full powers of substitution and revocation, to prosecute this application and to transact all business in the Patent Office connected therewith; and we (I) hereby request that all correspondence regarding this application be sent to the firm of PEARNE, GORDON, McCOY & GRANGER whose Post Office Address is : 1200 Leader Building Cleveland, Ohio 44114.

We (I) declare that all statements made herein of our (my) own knowledge are true and that all statements made on information and belief are believed to be true ; and future that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such wilful false statements may jeopardise the validity of the application or any patent issuing thereon.

1-00
CROCHON Elisabeth

NAME OF FIRST SOLE INVENTOR



Signature of Inventor

03 mai 1999

Date

Residence : 54 rue du Houchardotte
33320 POISSAT. FRX
FRANCE

Citizen of : Française

Post Office Address : The same as residence

2-00

VACHERAND François

NAME OF SECOND INVENTOR

F. Vacherand

Signature of Inventor

03 mai 1999

Date

Residence : 8, rue de Metz

38800 Le Pont de Claix FRX
France

Citizen of : Française

Post Office Address : The same as residence

Residence : _____

Citizen of : _____

Post Office Address : The same as residence

Residence : _____

Citizen of : _____

Post Office Address : The same as residence

Residence : _____

Citizen of : _____

Post Office Address : The same as residence

NAME OF THIRD INVENTOR

Signature of Inventor

Date

NAME OF FOURTH INVENTOR

Signature of Inventor

Date

NAME OF FIFTH INVENTOR

Signature of Inventor

Date